Safety Data Sheet

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Section 1: Product and Company Identification

Product Name: Manufacturer: Telephone Number: Address:



Prepared: 01/17/2019

Recommended use of Chemical and restrictions on uses advised against:

This product is used in industrial manufacturing, particularly in:

Ceramics Borosilicate glass Fiberglass

Section 2: Hazards Identification

2.1 Classification Of substance:

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Reproductive toxicity (Category 2) H361 Suspected of damaging fertility or the unborn child

2.2 GHS Label Elements

Pictogram Signal Word Warning



Hazard Statements

H361 Suspected of damaging fertility or the unborn child

Precautionary Statements

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P281 Use personal protective equipment as required.

P308/P313 If exposed or concerned: get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container to an approved waste disposal plant.

Emergency Overview:

Odor, Color, Grade: Light yellow liquid General Physical Form: Liquid

Immediate health, physical, and environmental hazards: The environmental properties of this product present a low environmental hazard. This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

2.3 Potential Health Effects

Inhalation is the most significant route of exposure in occupational and other settings. Dermal exposure is not usually a concern because it is poorly absorbed through intact skin.

Inhalation

Occasional mild irritation effect to nose and throat may occur from inhalation of dusts at levels higher than 10 mg/m³.

Eye Contact

Non irritating to eyes in normal industrial use.

Skin contact

Does not cause irritation to intact skin.

Ingestion

Products containing IM18B are not intended for ingestion.

Other

According to the U.S. Environmental Protection Agency this substance presents concerns for neurotoxicity and Specific Target Organ Toxicity (Lungs) when applied to particles.

Section 3: Composition/Ingredients

IngredientC.A.S. No.OSHA PELACGIH TLV% by WeightBoric Acid (H3BO3),59802-07-2NANA>98%Isooctadecyl Esters

Section 4: First Aid Measures

4.1 First Aid Procedures

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye First Aid: Flush eyes with clean, lukewarm water for 15 minutes. Obtain medical attention if irritation develops. Seek medical attention if symptoms persist.

Skin First Aid: Remove contaminated clothing; wash affected area well with soap and water. Launder well before use. Seek medical attention if symptoms persist.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

Inhalation First Aid: Move out of area into fresh air. Get immediate medical attention if cough or other symptoms develop.

Ingestion First Aid: Get immediate medical attention. Never induce vomiting by giving anything by mouth to an unconscious person.

Section 5: Fire Fighting Measures

5.1 Flammable Properties

Autoignition Temperature: Not Applicable
Flash Point (TCC): Not determined
Flammable Limits LEL: Not Determined
Not Determined

5.2 Extinguishing Media

Foam, CO₂, Dry Chemical, Water Spray

5.3 Protection of Fire Fighters

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and self-contained breathing apparatus (SCBA). Use caution when using water as frothing may occur and thereby increasing fire intensity.

Unusual Fire and Explosion Hazards: No unusual fire or explosion hazards are anticipated.

Sensitivity to Explosion by Mechanical Impact: None expected

Sensitivity to Explosion by Static Discharge: None expected

Conditions of flammability: Material will burn; avoid sources of ignition and temperatures that are within range of the flash point.

Note: See 'Stability and Reactivity (Section 10) for hazardous combustion and thermal decomposition information.

Section 6: Accidental Release Measures

Accidental Release Measures:

General: This material should be prevented from contaminating soil or from sewerage and drainage systems and bodies of water. Isolate hazard/spill area. Keep unnecessary and unprotected personnel from entering area. If not contaminated with debris, return to original container.

Small Spill: Absorb spill with inert material, then place in chemical waste container.

Large Spill: Shut of leak, if safe to do so. Clean up spills immediately, observing precautions in Protective equipment section. Contain spilled liquid with sand or earth. Retain contaminated water and soil for removal and treatment.

Section 7: Handling and Storage

7.1 Handling

This material does not present a significant skin and eye hazard. Skin and eye contact should be prevented as good industrial hygiene practice. Wearing of protective gloves and eye protection is recommended. Always establish the practice of washing arms and hands after handling.

7.2 Storage

Store in a cool, dry and well ventilated area. Avoid contact or exposure to incompatible substances. Avoid areas where there are ignition sources.

Section 8: Exposure Controls/Personal Protection

8.1 Control parameters

Occupational exposure limits for dust are treated by OSHA, Cal OSHA and ACGIH as "Particulate Not Otherwise Classified" or "Nuisance Dust".

Respect regulatory provisions for dust (total and respirable).

ACGIH/TLV 10 mg/m³
Cal OSHA/PEL 10 mg/m³
OSHA/PEL (total dust) 15 mg/m³
OSHA/PEL (respirable dust) 5 mg/m³

DNEL values

Exposure pattern	Type/site effect	Exposure Route	DNEL value
DNEL For Workers			
Long term	Systemic	Inhalation	8.3 mg BA/m ³
Long term	Systemic	Dermal	3924800 mg BA/day
_	•		
DNEL for the general public			
Acute	Systemic	Oral	0.98 mg BA/kg bw/day
Long term	Systemic	Dermal (external)	196 mg BA/kg bw/day
Long term	Systemic	Dermal (systemic)	0.98 mg BA/kg bw/day
Long term	Systemic	Inhalation	4.15 mg BA/m ³
Long term	Systemic	Oral	0.98 mg BA/kg bw/day

PNEC values

PNEC add, freshwater marine water = 1.35 mg B/L

PNEC add, aqua intermittent = 9.1 mg B/L

PNEC add, freshwater sediment, marine water sediment = 1.8 mg B/kg sediment dry weight

PNEC add, STP = 1.75 mg B/L

8.2 Exposure Controls

Sources of fine spray, mist or vapor should be controlled with local exhaust ventilation.

8.3 Personal Protection Equipment (PPE)

8.3.1 Eye/Face Protection

Always use safety glasses. Where contact with the eyes is likely, use chemical goggles.

8.3.2 Skin Protection

Wear impervious Gloves and chemical protective clothing to prevent contact with skin.

8.3.3 Respiratory Protection

A NISOH approved APF 10 must be worn.

8.3.4 Prevention of Swallowing

Do not swallow

8.3 Exposure Guidelines

None Established

Section 9: Physical and Chemical Properties

Odor, Color, Grade **General Physical Form** Autoignition temperature Flash Point (TCC) Flammable Limits—LEL Flammable Limits—UEL **Melting Point** Density Vapor Density Vapor Pressure **Specific Gravity** рΗ **Melting Point** Solubility Water **Evaporation rate Percent Volatile** Viscosity



Section 10: Stability and Reactivity

Stability: Stable

Materials and Conditions to Avoid: Avoid contact with strong reducing agents

Hazardous Polymerization: Hazardous Polymerization will not occur.

Hazardous Decomposition or By-Products: Oxide

Strong Oxidizer: No

Section 11: Toxicological Information

According to the U.S. Environmental Protection Agency this substance presents concerns for neurotoxicity and Specific Target Organ Toxicity (Lungs) when applied to particles.

Section 12: Ecological Information

Not determined

Section 13: Disposal Considerations

Waste Disposal Method:

Since regulations vary, consult applicable regulations or authorities before disposal.

Section 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO. DOT Shipping Name: Not regulated

Hazard Class NA
Packing Group NA
UN/NA No. NA
DOT Labels None
DOT Placard (bulk) None

Section 15: Regulatory Information

311/312 Hazard Categories:

• SARA 311/312 Chronic Health Not determined

SARA 311/312 Acute Health hazard Irritant
 SARA 311/312 Fire hazard No
 SARA 311/312 Sudden Pressure No
 SARA 311/312 Reactivity Hazard No

Section 302 – Extremely Hazardous Ingredient(s) None

CERCLA Hazardous Substances(s)

None

Section 313 Toxic Chemicals None

NJ Environmental Hazardous Substances List No

Other States Listings Not to our knowledge

California Proposition 65 Ingredients None

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Section 16: Other Information

NFPA Hazard Classification

Health: 2 Flammability: 2 Reactivity: 1

Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent

physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Level: Rev 6, 2/12/2019

